






PART#	WIRE RANGE CLASS B,C,D	WIRE RANGE CLASS K,M,I	INTERNAL HEX SIZE	L	W	H
ITG-6	6 - 14 AWG	6 - 14 AWG	1/8	1.12	1.19	1.43
ITG-1	1 - 10 AWG	2 - 10 AWG	3/16	1.62	1.50	1.75
ITG-3/0	3/0 - 4 AWG	2/0 - 2 AWG	3/16	1.84	1.60	1.85

NOTES:

1. CONNECTOR MANUFACTURED FROM 6061-T6 ALUMINUM ALLOY.
2. UL LISTED PER UL486A/B SPECIFICATIONS FOR 600V.
3. RATED FOR 90°C COPPER CONDUCTOR.
4. COLD TEMPERATURE RATED TO -45°C.
5. HIGH DIELECTRIC STRENGTH INSULATION IS ABRASION, CHEMICAL AND UV RESISTANT.

CONTACT NSI FOR SALES @ 800.321.5847

			POLARIS SALES . CO . INC	
PROPRIETARY AND CONFIDENTIAL			11625 PROSPEROUS DRIVE ODESSA, FL 33556	
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF POLARIS SALES CO. INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF POLARIS SALES CO. INC. IS PROHIBITED.			TITLE: INSULATED TWO HOLE CONNECTOR SERIES GREY FINE STRANDED	
	NAME	DATE	DWG. NO.	
DRAWN BY	S.PARRY	8/10/2026	ITG-SERIES	
MATERIAL: 6061-T6511 ALUMINUM			SCALE: 1:1	SHEET: 1 OF 1